




HSIP2D-300

Dome Camera with IR (True Day & Night)

KEY FEATURES

1. H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
2. Support ONVIF 2.4
3. 2.8~12mm (3MP) Varifocal Lens
4. 3D NR , White Balance, FLK(Flicker Control)
5. Support (Defog Mode, WDR, Motion Detection)



CAMERA

Model Name	HSIP2D-300
Image Sensor	1/2.9" Low Illumination CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1985(H)*1105(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional

LENS

Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Varifocal
Pixels	3MP

Night Vision

Infrared LED	14μ x 24PCS
Infrared Distance	30M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

* The product design and dimensions may change without previous notice to enhance the performance.



HSIP2D-300

Dome Camera with IR (True Day & Night)

CAMERA FEATUERS

Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
Defog Mode	Support
ROI	Support
BLC	Support
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Language	English, Bulgarian, Polish, Farsi, German,Italian,Nederlands Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Chinese.

INTERFACE

Audio	Optional
SD Card Slot	Optional, Support Max 128GB

GENERAL

Housing	Metal , IP66
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 1100mA
Dimension	Ø131 x 93(H) mm
Weight	800g

* The product design and dimensions may change without previous notice to enhance the performance.

HSIP2D-300

Dome Camera with IR (True Day & Night)



NETWORK

Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	1920*1080@30fps
Sub Stream 1	720*480@30fps
Tri Stream	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad

* The product design and dimensions may change without previous notice to enhance the performance.