



## HSIP2B-300

Bullet Camera with IR

### KEY FEATURES

1. H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
2. Colour / B&W (IR-CUT)
3. 3D NR (Noise Reduction), FLK (Flicker Control)
4. Motion Detection, BLC Support
5. 2.8~12mm, 3MP Varifocal Lens
6. Support ONVIF



CAMERA	
Model No.	HSIP2B-300
Image Sensor	1/2.9" Low Illumination CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1985(H)*1105(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
LENS	
Focus Length	2.8-12mm
Focus Control	Manual
Lens Type	Varifocal
Pixels	3MP
Night Vision	
Infrared LED	42μ x 6PCS
Infrared Distance	60M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control

\* The product design and dimensions may change without previous notice to enhance the performance.

## HSIP2B-300

Bullet Camera with IR



### CAMERA FEATURES

Day/Night	Color/ B&W (IR-CUT )
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control)
BLC	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/NAS/CMS/Web
Defog Mode	Support
ROI	Support
WDR	Support
Language	English, Bulgarian, Polish, Farsi, German, Russian, French,Korean, Portuguese, Japanese, Turkish, Spanish, Italian,Chinese.

### GENERAL

Housing	Metal , IP66
Anti-cut Bracket	YES
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C~ +60°C RH95% Max
Power Source	DC12V±10%, 1150mA
Dimension	312(W) x 133(H) x102(D)mm
Weight	1800g

\* The product design and dimensions may change without previous notice to enhance the performance.

## HSIP2B-300

Bullet Camera with IR



NETWORK	
Ethernet	RJ-45 (10/100Base-T)
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP, RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	1920*1080@30fps
Main Stream 2	1280*720@30fps
Sub Stream 1	720*480@30fps
Tri Stream	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad

\* The product design and dimensions may change without previous notice to enhance the performance.